



Ball valve

- PE 100 SDR 11 (ISO S5) - d20 up to d225
- 10 bar Gas / 16 bar Water
- d20 - d110 in accordance with DVGW GW336 / DVGW VP302 / DVGW W364
- d160 up to d225 are supplied with base plate and straps
- d1 = diameter of bore
- Regarding pressure rate and application local standards and regulations have to be considered
- *In accordance with ANSI B16.40

d (mm)	Code	SP	Weight (kg)	Weight (kg)	L1 (mm)	t (mm)	H (mm)	H1 (mm)	d1 (mm)
20	193 103 206	1	0.487	1	264	72	134	96	23
25	193 103 207	1	0.490	1	264	72	134	96	23
32	193 103 208	1	0.506	1	274	76	134	96	23
40	193 103 209	1	0.616	1	301	85	142	100	30
50	193 103 210	1	0.829	1	327	92	156	107	38
63	193 103 211	1	1.174	1	350	101	173	114	48
75	193 103 212	1	1.434	1	376	114	173	114	48
90	193 103 213	1	2.918	3	439	128	240	158	68
110	193 103 214	1	4.416	5	497	148	267	171	83
125	193 103 040	0	4.220	4	405	112	365	280	64
160	193 103 042	1	10.541	10	450	117	481	364	92
180	193 103 043	0	10.524	10	540	123	481	364	92
200	193 103 044	1	12.023	11	540	123	481	364	92
*	225	193 103 045	24.400	19	877	240	755	540	120

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>